

## FUSE overview for 110-120V units

Nov. 2021

T = timelag / slowblow fuse. "F" = Fast acting fuse. All fuses must be 250V and UL-listed types.

Recommended fuse type are Schurter FST series, except: \*: Schurter SPT series and \*\*: Busmann S505

NB. Note regarding "audiophile" fuses:

A fuse is actually a quite complex component, which has to both protect the device against overvoltage, spikes and intermittent dropouts – and to protect the device against consequential damage if an internal fault occurs.

If replacing a fuse, it is very important to replace with a quality fuse of same rated current, characteristics, rated voltage, breaking capacity and a suitable safety classification. It is unfortunately our impression that not all special "Hi-End" fuses comply to these parameters and have the required safety classifications.

You will not automatically loose warranty if using other fuses, but we might reject a warranty claim if the unit fails or is damaged due to use of wrong – or questionable quality – fuse types.

| Product                   | Location            | Qty | value  | size   |
|---------------------------|---------------------|-----|--------|--------|
| Antileon EVO Mono         | Rear panel          | 1   | 15AT   | 6.3x32 |
|                           | F501                | 1   | 400mAT | 5x20   |
|                           | F502,F503           | 2   | 1AF    | 5x20   |
|                           | F504                | 1   | 1AT    | 5x20   |
|                           | F1, F2 (cap.boards) | 4   | 1AT    | 5x20   |
| Antileon EVO Stereo       | Rear panel          | 2   | 10AT   | 6.3x32 |
|                           | F501                | 1   | 400mAT | 5x20   |
|                           | F502,F503           | 2   | 1AF    | 5x20   |
|                           | F504                | 1   | 1AT    | 5x20   |
|                           | F1, F2 (cap.boards) | 4   | 1AT    | 5x20   |
| Antileon Signature Mono   | Rear panel          | 1   | 15AT   | 6.3x32 |
|                           | F501                | 1   | 315mAT | 5x20   |
|                           | F502,F503,F504      | 3   | 1AF    | 5x20   |
| Antileon Signature Stereo | Rear panel          | 2   | 10AT   | 6.3x32 |
|                           | F501                | 1   | 315mAT | 5x20   |
|                           | F502,F503,F504      | 3   | 1AF    | 5x20   |
| Athena                    | Rear panel          | 2   | 1AT    | 5x20   |
|                           | F1                  | 1   | 63mAT  | 5x20   |
|                           | F2, F3              | 2   | 1AT    | 5x20   |
| Atilla                    | Rear panel          | 1   | 6.3AT  | 5x20   |
| Colosseum                 | Rear panel          | 1   | T16A * | 6.3x32 |
|                           | F1                  | 1   | 100mAT | 5x20   |
|                           | F2                  | 1   | 1AT    | 5x20   |
| Diablo (250W)             | Rear panel          | 1   | 12.5AT | 5x20   |
|                           | F101-102, F201-202  | 4   | 630mAT | 5x20   |
| Diablo 300                | Rear panel          | 1   | 12.5AT | 5x20   |
|                           | F101-102, F201-202  | 4   | 630mAT | 5x20   |
|                           | F3                  | 1   | 1AT    | 5x20   |
|                           | F4                  | 1   | 63mAT  | 5x20   |

## FUSE overview for 110-120V units

Nov. 2021

T = timelag / slowblow fuse. "F" = Fast acting fuse. All fuses must be 250V and UL-listed types.

Recommended fuse type are Schurter FST series, except: \*: Schurter SPT series and \*\*: Busmann S505

NB. Note regarding "audiophile" fuses:

A fuse is actually a quite complex component, which has to both protect the device against overvoltage, spikes and intermittent dropouts – and to protect the device against consequential damage if an internal fault occurs.

If replacing a fuse, it is very important to replace with a quality fuse of same rated current, characteristics, rated voltage, breaking capacity and a suitable safety classification. It is unfortunately our impression that not all special "Hi-End" fuses comply to these parameters and have the required safety classifications.

You will not automatically loose warranty if using other fuses, but we might reject a warranty claim if the unit fails or is damaged due to use of wrong – or questionable quality – fuse types.

| Product              | Location               | Qty | value     | size   |
|----------------------|------------------------|-----|-----------|--------|
| Diablo 120           | Rear panel             | 1   | 6.3AT     | 5x20   |
|                      | F101-102, F201-202     | 4   | 630mAT    | 5x20   |
|                      | F3                     | 1   | 1AT       | 5x20   |
|                      | F4                     | 1   | 63mAT     | 5x20   |
|                      | F5                     | 1   | 1.6AT     | 5x20   |
| Ethos                | Rear panel             | 2   | 800mAT    | 5x20   |
|                      | F1                     | 1   | 63mAT     | 5x20   |
|                      | F2, F3                 | 2   | 1.6AT     | 5x20   |
|                      | F4                     | 0   | empty     |        |
|                      | F5, F6                 | 2   | 400mAT    | 5x20   |
| Essence Preamplifier | Rear panel             | 2   | 1AT       | 5x20   |
|                      | F1                     | 0   | empty     |        |
|                      | F2, F3                 | 2   | 500mAT    | 5x20   |
|                      | F4                     | 1   | 63mAT     | 5x20   |
|                      | F5                     | 1   | 1AT       | 5x20   |
|                      | F6                     | 1   | 1.6AT     | 5x20   |
| Essence Power        | Rear panel             | 1   | 10AT *    | 6.3x32 |
|                      | F101-102, F201-202     | 4   | 630mAT    | 5x20   |
|                      | F3                     | 1   | 1AT       | 5x20   |
|                      | F4                     | 1   | 63mAT     | 5x20   |
| Kalliope             | Rear panel             | 2   | 1AT       | 5x20   |
|                      | F1                     | 1   | 63mAT     | 5x20   |
|                      | F2                     | 1   | 1AT       | 5x20   |
|                      | F3                     | 1   | 2AT       | 5x20   |
| Kodo                 | Rear panel, main       | 2   | 12.5AT ** | 5x20   |
|                      | Rear panel, stby       | 2   | 200mAT    | 5x20   |
| Legato Legacy SA     | Rear panel             | 2   | 1AT       | 5x20   |
|                      | F1, F2 (analog supply) | 4   | 315mAT    | 5x20   |
|                      | F1                     | 1   | 63mAT     | 5x20   |
|                      | F2, F3                 | 2   | 1AT       | 5x20   |
| Mephisto Solo        | Rear panel             | 1   | 15AT      | 6.3x32 |
|                      | F1, F2                 | 2   | 63mAT     | 5x20   |
|                      | F3                     | 1   | 1AT       | 5x20   |
|                      | F4                     | 1   | 1.6AT     | 5x20   |

## FUSE overview for 110-120V units

Nov. 2021

T = timelag / slowblow fuse. "F" = Fast acting fuse. All fuses must be 250V and UL-listed types.

Recommended fuse type are Schurter FST series, except: \*: Schurter SPT series and \*\*: Busmann S505

NB. Note regarding "audiophile" fuses:

A fuse is actually a quite complex component, which has to both protect the device against overvoltage, spikes and intermittent dropouts – and to protect the device against consequential damage if an internal fault occurs.

If replacing a fuse, it is very important to replace with a quality fuse of same rated current, characteristics, rated voltage, breaking capacity and a suitable safety classification. It is unfortunately our impression that not all special "Hi-End" fuses comply to these parameters and have the required safety classifications.

You will not automatically loose warranty if using other fuses, but we might reject a warranty claim if the unit fails or is damaged due to use of wrong – or questionable quality – fuse types.

| Product              | Location               | Qty | value  | size   |
|----------------------|------------------------|-----|--------|--------|
| Mephisto Stereo      | Rear panel             | 2   | 10AT   | 6.3x32 |
|                      | F1, F2                 | 2   | 63mAT  | 5x20   |
|                      | F3                     | 1   | 1AT    | 5x20   |
|                      | F4                     | 1   | 1.6AT  | 5x20   |
| Mikado / - Signature | Rear panel             | 2   | 630mAT | 5x20   |
|                      | F1                     | 1   | 125mAT | 5x20   |
|                      | F2                     | 1   | 100mAT | 5x20   |
| Mirage               | Rear panel             | 2   | 1AT    | 5x20   |
|                      | F1                     | 1   | 400mAT | 5x20   |
| Pandora              | Rear panel             | 2   | 1AT    | 5x20   |
|                      | F1, F2 (analog supply) | 4   | 315mAT | 5x20   |
|                      | F1                     | 1   | 63mAT  | 5x20   |
|                      | F2, F3                 | 1   | 1AT    | 5x20   |
| Poseidon & Pendragon | Rear panel, main       | 2   | 12.5AT | 5x20   |
|                      | Rear panel, stby       | 2   | 200mAT | 5x20   |
| Scorpio / -S         | Rear panel             | 2   | 630mAT | 5x20   |
|                      | F1                     | 1   | 250mAT | 5x20   |
| Sonett               | F1-2, F4-5             | 4   | 315mAT | 5x20   |
|                      | F3, F6                 | 0   | empty  |        |
| Trident / Trident II | Rear panel, main       | 2   | 12.5AT | 5x20   |
|                      | Rear panel, stby       | 2   | 200mAT | 5x20   |
| Zena                 | Rear panel             | 2   | 1AT    | 5x20   |
|                      | F1                     | 0   | empty  |        |
|                      | F2, F3                 | 2   | 500mAT | 5x20   |
|                      | F4                     | 1   | 63mAT  | 5x20   |
|                      | F5                     | 1   | 1AT    | 5x20   |
|                      | F6                     | 1   | 1.6AT  | 5x20   |