GRYPHON AUDIO DESIGNS

Gryphon Zena DAC Windows USB driver installation Revision 0

Gryphon Zena DAC module USB Kernel Streaming / ASIO driver installation:

The **Zena DAC USB Kernel Streaming driver** supports playback of the following formats:

PCM: up to 32-bit with supported Sample Rates: 44.1kHz, 48kHz, 96kHz, 176.4kHz, 192kHz, 352.8kHz and 384kHz.

DSD: DSD64 (2.8224MHz) and DSD128 (5.64548MHz) with DoP*, DSD native mode not supported!

The **Zena DAC USB Windows ASIO driver** supports playback of the following formats:

PCM: up to 32-bit with supported Sample Rates: 44.1kHz, 48kHz, 96kHz, 176.4kHz, 192kHz, 352.8kHz and 384kHz.

DSD: DSD64 (2.8224MHz), DSD128 (5.64548MHz), DSD256 (11.2896MHz) and DSD512 (22.5792MHz).
Up to DSD128 with DoP*.
Up to DSD512 in DSD native mode.

1. Download and install the Zena DAC USB combined Kernel Streaming / ASIO driver for Windows Win7, Win8 and Windows10 from the www.gryphon-audio.com web site.

2. Before running the setup file, please temporarily deactivate your antivirus shield for about 10 minutes and then:

   Run the downloaded file: "**Zena_setup_Win.exe**"
   (for both 32bit and 64bit Windows installation)

   Follow the instructions on the screen.

*DoP explaned: DSD over PCM (DoP) packs DSD into a PCM-like signal for bit streaming.

GRYPHON AUDIO DESIGNS
INDUSTRIVEJ 10B, 8680 RY, DENMARK, TEL (45)86891200, FAX (45)86891277, WWW.GRYPHON-AUDIO.DK